

Technical data and features

Power supply: 115VAC ±10%; 50/60 Hz
 Branch circuit protection (by others): 15 A
 Cable type: 14 AWG (12 Max) [max. 3 x 1.5 mm²]

Power consumption without external accessories:
 Stand-By-Mode: 5.6W
 Automatic-Mode: max.60W

General information:
 Temperature range: 0 - 104° F [0 - 40° C]
 Operating noise of operator: max.55 dB (A)
 Door panel height: max. 118" [max. 3000 mm]
 Door panel weight: 44 lbs - 175 lbs [20 kg - 80 kg]

Weight of operator:	max.passage width	Operator length without cover	Weight of operator
		34.4" [875 mm]	68.9" [1750 mm]
	39.4" [1000 mm]	78.7" [2000 mm]	20.7 lbs [9.4 kg]
	44.3" [1125 mm]	88.6" [2250 mm]	22.4 lbs [10.2 kg]

FCC 15.105 (a)
NOTE:

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.